



[ Innovative Technology ]

# Concealed Valves

NEW!



## ● Variable concealed part for installation depth 35 to 105 mm - ready-to-install

Easy to install, to use and to handle by means of a 4x adjustable wall pipe and intermediate spindle piece made of brass. Stepless adjustable polystyrene protection sleeve.

**Casing made of dezincification hot-pressed brass**

Double safety against aggressive water and extremely durable are our concealed NILplus valves, with casings made of hot-pressed DZR brass.

**Sanitary grease chamber head with short valve spindle**

Smooth running, tough, maintenance free

... or as a comfortable alternative:

**Sanitary ceramic head part with short valve spindle**

Extremely easy to open and close with just a 1/4 of a turn

## ● Exposed part with the new printable NILplus grip

Head part with provided thread and spring supported spindle operation, 24 mm high wall rosette  $\varnothing$  70 mm and the newly developed NILplus grip.

**NILplus | Logo:** Have your personal company logo printed on our concealed valves. Minimum order quantity just 10 concealed NILplus valves. Simply add -50 to the order-no., e.g. 8800-50.

## ● NIL taps are manufactured according to norms, environmentally friendly, tested and certified

Material acc. to DIN EN 50930. KTW - approved plastic and rubber parts. Valve dimensions acc. to DIN 3512. Hydraulic values according to DIN EN 1213.

Noise behaviour according to DIN EN ISO 2822.

## ● NILplus concealed valves: Cut to size ... fix it ... and that's it!



Innovative Technology

# Concealed Valves

NEW!

Besides the new NILplus grip 3 additional versions are available:



NILplus grip



Acrylic grip



Lock shield device



Closed cap

Please choose!

### Concealed valves with sanitary grease chamber head



### Concealed valves with sanitary ceramic head

Concealed valves with sanitary grease chamber head and thread connection on both sides	Order-no.
NILplus valve DN 15 with 1/2" internal thread on both sides and with NILplus grip	8800
as above, however DN 20 with 3/4" internal thread	8810
as above, however DN 25 with 1" internal thread	8820
Concealed valves with sanitary grease chamber head and soldering connection on both sides	Order-no.
NILplus valve DN 15 with soldering connection ø 15 mm on both sides and with NILplus grip	8830
as above, however DN 15 with soldering connection ø 18 mm	8840
as above, however DN 20 with soldering connection ø 22 mm	8850
as above, however DN 25 with soldering connection ø 28 mm	8860
Concealed valves with sanitary ceramic head and thread connection on both sides	Order-no.
NILplus valve DN 15 with 1/2" internal thread on both sides and with NILplus grip	8900
as above, however DN 20 with 3/4" internal thread	8910
Concealed valves with sanitary ceramic head and soldering connection on both sides	Oder-no.
NILplus valve DN 15 with soldering connection ø 15 mm on both sides and with NILplus grip	8930
as above, however DN 15 with soldering connection ø 18 mm	8940
as above, however DN 20 with soldering connection ø 22 mm	8950

NILplus concealed valves are also available with acrylic grip, lock shield device and closed cap.



FRIEDRICH GAMPPER KG

P.O. Box 1164 • D - 71534 Murrhardt  
Tel. +49 (0) 7192-971-0 • Fax 971-105  
www.nil-gampper.de • info@nil-gampper.de

